



SINCE 1909
JAPAN

KDK Instant Home Shower

Product Specifications

Model	TG3AD1	TG3AE1	TG3BL1
Voltage	230V a.c. 50Hz	230V a.c. 50Hz	230V a.c. 50Hz
Power Consumption	3300 W	3300 W	3300 W
Electric Temperature Control	Inlet Water Temp. PO (Off), 32 °C - 45 °C	-	-
Electric Power Control	-	Min ~ 3300 W	Inlet Water Temp. (Off), 1000 W ~ 3300 W
Min. Water Pressure	9.8 kPa / 0.1 kgf/cm ² / 1.42 psi / 0.098 bar	9.8 kPa / 0.1 kgf/cm ² / 1.42 psi / 0.098 bar	9.8 kPa / 0.1 kgf/cm ² / 1.42 psi / 0.098 bar
Max. Water Pressure	380 kPa / 3.87 kgf/cm ² / 55 psi / 3.8 bar	380 kPa / 3.87 kgf/cm ² / 55 psi / 3.8 bar	380 kPa / 3.87 kgf/cm ² / 55 psi / 3.8 bar
Weight	1.9kg	1.5 kg	1.6 kg
Outlet System	Single Point System (Open Outlet)	Single Point System (Open Outlet)	Single Point System (Open Outlet)
Width	210 mm	210 mm	190 mm
Depth	78 mm	78 mm	82 mm
Height	385 mm	385 mm	380 mm
Shower Head	3 Way, Rail Rod	3 Way, Rail Rod	3 Way, Rail Rod
Heater Tank	Copper	Copper	Reinforced Polyamide
On/Off Control	One Push On/Off	One Push On/Off	Analog Control Knob